



AS50e

Electric rammers

Emission-free - For all classic rammer work

With the battery tamper, the operator works completely free of emissions. The battery-powered rammer is not only an asset when compacting soil in trenches and city centres, but also relieves the operator and the environment on every construction site. One battery charge is sufficient to do all the work of an average working day. The battery can be changed without tools in just a few easy steps and can be used for a wide range of other Wacker Neuson construction equipment.

Highlights

- Low energy costs
- No exhaust emissions
- Maintenance-free electric motor
- Starts with a push of a button
- One battery for all products

Technical Data

Electrical - Output Details		Operating weight	156.5 lb
Nominal current	41.00 A	Stroke at tamper	1.5 "
Nominal voltage	51.0 V	Motor	
Nominal power [P]	2.10 KW	Motor type	Asynchronous motor
Mechanical - Output Details		Environment Data	
Number of blows	680.0 1/min	Degree of protection	IP23D
Area capacity	1,582.3 ft2/h	Storage temperature range	-22 - 122 °F
Forward Running	0.5 fps	Operating temperature range	32 - 113 °F
Power of impact	3,596.9 lbf	Sound power LWA, guaranteed	108.0 dB(A)
Mechanical Details		Sound power LWA (Standard)	EN 500-4
Length	24.0 "	HAV summation (average value)	25.3 ft/s2
Length Ramming Shoe	13.4 "	HAV summation (Standard)	EN 500-4
Width	14.3 "	Operating Fluids	
Width Ramming Shoe	11.0 "	Oil specification	SAE 10W-40
Height	41.3 "	Oil volume	0.185 gal US
Weight	135.58 lb	Lubrication intervall	250.0 h

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes.